

CoroMill® 415

Small diameter, high feed face milling cutter

Application

- High feed face milling
- Plunge milling
- Ramping
- Roughing to semi-finishing
- Helical interpolation
- Profiling

ISO application area:



Benefits and features

- Versatile tool suitable for a wide range of applications
- Coolant channels for optimized chip evacuation
- Can be combined with the Coromant EH coupling and Silent Tools™ damped adaptors for vibration-free machining, high reliability and a significant productivity gain
- Unique iLock™ insert seat interface resulting in less scrap workpieces. The iLock™ insert seat also makes the small inserts easier to handle.
- Tailor made options available



www.sandvik.coromant.com/coromill415

Couplings

- Cylindrical shank
- Coromant EH
- Threaded coupling

Inserts

- Four cutting edges
- The unique iLock™ solution provides easy and accurate insert indexing, increased reliability and considerably improved tool life




I26



I29


CoroMill® 415 face milling cutter

Cylindrical shank - Internal coolant supply



KAPR

15°



DC	CZCMS	APMX _{EFW}	APMX _{FFW}	RMPX	CNSC	Ordering code	Dimensions, mm				CICT	MIID			
							DCON	DCX	BD ₁	LF	NM	KG	RPMX		
4.6	05	12	3.0	0.85	0.85°	1	2			12.0	13.0	11.0	23600	2	415N-050206M
7.6	05	12	3.0	0.85	0.97°	1	3			12.0	16.0	12.0	21300	3	415N-050206M
11.6	05	16	3.0	0.85	0.62°	1	3			16.0	20.0	16.0	19000	3	415N-050206M
	05	16	3.0	0.85	0.62°	1	4			16.0	20.0	16.0	19000	4	415N-050206M
	05	16	3.0	0.85	0.62°	1	5			16.0	20.0	16.0	19000	5	415N-050206M
13.5	07	20	4.5	1.20	0.61°	1	4			20.0	25.0	19.0	15700	4	415N-070310M
16.6	05	20	3.0	0.85	0.64°	1	5			20.0	25.0	21.0	17000	5	415N-050206M
20.5	07	25	4.5	1.20	0.63°	1	5			25.0	32.0	26.0	13900	5	415N-070310M

	Spare parts
	Insert screw
05	5513 020-28
07	5513 020-56

For complete list of spare parts, see www.sandvik.coromant.com



I29



L4



N22




N9



N15


CoroMill® 415 face milling cutter

Coromant EH coupling - Internal coolant supply



KAPR

15°



DC CZC _{MS}	E12	3.0	0.85	0.85°	1	2	Ordering code	Dimensions, mm					CICT	MIID			
								DCON	DCX	BD ₁	LF	(NM)	(KG)				
4.6	05	E12	3.0	0.85	0.85°	1	415-13EH12-05H	11.7	13.0	11.0	25.0	0.6	0.14	23600	2	415N-050206M	
7.6	05	E16	3.0	0.85	0.97°	1	3	415-16EH16-05H	15.5	16.0	12.0	30.0	0.6	0.18	21300	3	415N-050206M
8.6	07	E16	4.5	1.20	0.56°	1	2	415-20EH16-07H	15.5	20.0	14.0	35.0	1.2	0.17	17500	2	415N-070310M
	07	E20	4.5	1.20	0.56°	1	2	415-20EH20-07H	19.3	20.0	14.0	35.0	1.2	0.19	17500	2	415N-070310M
11.6	05	E16	3.0	0.85	0.62°	1	4	415-20EH16-05M	15.5	20.0	16.0	30.0	0.6	0.05	19000	4	415N-050206M
	05	E20	3.0	0.85	0.62°	1	4	415-20EH20-05M	19.3	20.0	16.0	32.0	0.6	0.07	19000	4	415N-050206M
	05	E16	3.0	0.85	0.62°	1	5	415-20EH16-05H	15.5	20.0	16.0	30.0	0.6	0.16	19000	5	415N-050206M
	05	E20	3.0	0.85	0.62°	1	5	415-20EH20-05H	19.3	20.0	16.0	32.0	0.6	0.19	19000	5	415N-050206M
13.5	07	E20	4.5	1.20	0.61°	1	3	415-25EH20-07M	19.3	25.0	19.0	35.0	1.2	0.08	15700	3	415N-070310M
	07	E25	4.5	1.20	0.61°	1	3	415-25EH25-07M	24.2	25.0	19.0	40.0	1.2	0.12	15700	3	415N-070310M
	07	E20	4.5	1.20	0.61°	1	4	415-25EH20-07H	19.3	25.0	19.0	35.0	1.2	0.20	15700	4	415N-070310M
	07	E25	4.5	1.20	0.61°	1	4	415-25EH25-07H	24.2	25.0	19.0	40.0	1.2	0.12	15700	4	415N-070310M
16.6	05	E20	3.0	0.85	0.64°	1	5	415-25EH20-05M	19.3	25.0	21.0	32.0	0.6	0.08	17000	5	415N-050206M
	05	E25	3.0	0.85	0.64°	1	5	415-25EH25-05M	24.2	25.0	21.0	35.0	0.6	0.12	17000	5	415N-050206M
	05	E20	3.0	0.85	0.64°	1	6	415-25EH20-05H	19.3	25.0	21.0	32.0	0.6	0.20	17000	6	415N-050206M
	05	E25	3.0	0.85	0.64°	1	6	415-25EH25-05H	24.2	25.0	21.0	35.0	0.6	0.24	17000	6	415N-050206M
20.5	07	E25	4.5	1.20	0.63°	1	4	415-32EH25-07M	24.2	32.0	26.0	40.0	1.2	0.27	13900	4	415N-070310M
	07	E25	4.5	1.20	0.63°	1	5	415-32EH25-07H	24.2	32.0	26.0	40.0	1.2	0.16	13900	5	415N-070310M
23.6	05	E25	3.0	0.85	0.65°	1	7	415-32EH25-05H	24.2	32.0	28.0	35.0	0.6	0.16	15000	7	415N-050206M

	Spare parts
	Insert screw
05	5513 020-28
07	5513 020-56

For complete list of spare parts, see www.sandvik.coromant.com



I29



L4



N22



N9




N15



N3


CoroMill® 415 face milling cutter

Threaded coupling - Internal coolant supply



KAPR

15°



							Dimensions, mm										
DC	CZC _{MS}	APMX _{EFW}	APMX _{FFW}	RMPX	CNSC	Ordering code	DCON	DCX	BD _t	LF	(NM)	(KG)	RPMX	CICT	MIID		
							12.8	13.0	11.0	25.0	0.6	0.02	23600	2	415N-050206M		
4.6	05	M8	3.0	0.85	0.85°	1	2	415-13T08-05H	12.8	16.0	12.0	25.0	0.6	0.03	21300	3	415N-050206M
7.6	05	M8	3.0	0.85	0.97°	1	3	415-16T08-05H	17.8	20.0	16.0	30.0	0.6	0.05	19000	5	415N-050206M
11.6	05	M10	3.0	0.85	0.62°	1	5	415-20T10-05H	20.8	25.0	19.0	38.0	1.2	0.09	15700	4	415N-070310M
13.5	07	M12	4.5	1.20	0.61°	1	4	415-25T12-07H	20.8	25.0	21.0	35.0	0.6	0.10	17000	6	415N-050206M
16.6	05	M12	3.0	0.85	0.64°	1	6	415-25T12-05H	28.8	32.0	26.0	40.0	1.2	0.19	13900	5	415N-070310M
20.5	07	M16	4.5	1.20	0.63°	1	5	415-32T16-07H									

	Spare parts
	Insert screw
05	5513 020-28
07	5513 020-56

For complete list of spare parts, see www.sandvik.coromant.com



N22




N9



N15

CoroMill® 415 insert for milling



				P	M	S	H	Dimensions, mm
		RE	Ordering code	1010 1030 1040 4240 S40T 1030 1040 4240 S30T 1030 H13A S30T S40T 1010 1030	IC LE S			
Medium	M30	05	0.60 415N-05 02 06M-M30	☆ ☆ ☆ ★ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆	5.0 3.8 2.21			
		07	1.00 415N-07 03 10M-M30	☆ ☆ ☆ ★ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆	7.0 5.0 3.07			

